



Model UR 101

Tripod model DRB

Conform to EN 795

- With securing device
- Working load limit: 500 kg
- Breaking force: 22 kN
- Closed height: 1.75 m (model DRB-9) or 2.05 m (model DRB-11)
- Weight: 14.3 kg (model DRB-9) or 19.0 kg (model DRB-11)

Technical data model DRB

Model	EAN-No. 4025092*	Height m
DRB-9 for REW-K	*165136	1340 - 2300
DRB-11 for REW-11	*281249	1790 - 2890
UR 101 pulley	*472340	-

Five leg anchor point model F-DRB

Conform to EN 795

- Including a beam of 2.3 m length
- Including the tripod and two additional legs and accessories
- Total weight 72 kg
- The tripod can be used separately.

Technical data model F-DRB

Model	EAN-No. 4025092*	Height m
F-DRB-5	*288699	1390 - 2210

Rescue winch model REW-K and model REW-11 Load winch model LAW-K

Conform to EN 1496 class B

- With integrated automatic brake c/w mounting bracket
- Working load limit: 180 kg
- Breaking force: 18 kN
- Galvanized steel rope (diameter: 6.3 mm)
- Weight 13 and 14 kg (model REW-K) or 22.5 and 25.5 kg (model REW-11).
- Incl. mounting bracket for tripod model DRB-9 or model DRB-11.
- Model LAW-K 25 for loads up to max. 250 kg



! Hook and pulley included.

Technical data models REW-K, REW-11 and LAW-K

Model	EAN-No. 4025092*	Length m
REW-K 20 for DRB-9	*165150	20
REW-K 25 for DRB-9	*165167	25
LAW-K 25	*347143	25
REW-11-25 for DRB-11	*281256	25
REW-11-35 for DRB-11	*281270	35
REW-11-45 for DRB-11	*281317	45
REW-11-50 for DRB-11	*281379	50